

SYKES PUMPS 



**THE UNIVAC
GP & WP
EXTENDED
LIFE RANGE**

**DELIVERING
PUMPING
SOLUTIONS
FOR OVER
150 YEARS**

THE UNIVAC GP & WP EXTENDED LIFE RANGE

ENDURING QUALITY FROM SYKES PUMPS

MULTI-PURPOSE SOLUTION:

- Standard sump pumping
- Slurry & semi solid material
- Well pointing - high vacuum pump capacity
- Dry running applications
- 24 hour reliability
- Designed for high ambient environments

MARKET SECTORS:

- Building & Construction - well pointing and sump pumping
- Water & Waste - over pumping and systems bypass
- Quarries & Mines - sump pumping
- Emergency Water Control - sump pumping
- Docks, Ports & Harbours - sump pumping and stabilisation of loads

PUMP OPTIONS:

- Bronze impeller and wear plates (standard)
- Stainless steel impeller and wear plates
- Mechanical seal
- Hand start engines (standard)
- Electric start engines
- Engine hour meter
- Engine protection system
- Alternative engine options
- Electric motor option
- Skid mounted chassis
- 2 wheel solid rubber tyre site trailer
- 4 wheel solid rubber tyre site trailer
- High speed road trailer
- Wide range of recommended accessories
- Silenced range option
- Extensive range available up to 12" (300mm) capacity
- Broad range of submersible pumps

SPECIFICATION/PERFORMANCE DATA

	GP50/75	GP80	GP100M	WP150-60	GP150M	GP200	GP200M
Engine Option (Alternative engine quotes available)	Lister AD1	Lister TR1	Lister TR2	Lister TR3	Lister TR3/ Deutz F3L912	Deutz F4L912	Deutz F6L912
Engine Power/Speed-KW/ RPM	4.3 @ 2500	6.7 @ 1800	13.1 @ 1800	20.20 @ 1800	20.2/31 @ 1800	40 @ 1800	57 @ 1800
Dimensions L x W x H (cms)	122 x 75 x 86	170 x 119 x 110	194 x 145 x 150	210 x 150 x 164	210 x 150 x 164	263 x 157 x 181	263 x 157 x 181
Solids Handling - mm	28	40	44	48	52	48	75
Weight - Kgs	188	425	907	919	1230	1440	1550
Max Head/Max Flow - m/l/s	28/15	24/34	31/45	35/77	38/90	36/138	43/161



GP50/75



GP80



GP100M



WP150-60



GP150M



GP200/GP200M

THE UNIVAC GP & WP EXTENDED LIFE RANGE

BUILDING ON 150 YEARS OF MARKET LEADING PUMPING SOLUTIONS

Sykes Pumps offers the 'extended life' specification (as standard) for markets needing ever more durable pumping performance.

The GP and WP range from Sykes Pumps offer General Purpose and Well Pointing specialised solutions to customers who demand quality, extended durability and value.

From 2" - 8" diameter (50mm - 200mm), Sykes Pumps offers a solution to a broad range of pumping needs.

Whether it is sump pumping, well pointing, pumping clean water or slurry material, Sykes Pumps will help define the optimal pumping solution.


Through our professional distributor and subsidiary network, we offer a comprehensive advisory service together with responsive spare parts and service support.


BENEFITS OF SYKES PUMPS:

- Experience - over 150 years British design evolution
- Local expertise - professional distributors with local regional Sykes Pumps engineers to support your specific needs
- Vacuum priming in excess of 9m* - vertical suction lift in under one minute even on 'snore'
- Fast automatic priming and re-priming (can run dry and then re-prime)
- Heavy duty internal pump bearings - exceptional long life
- Heavy duty pump volute supplied from UK foundry
- Internals supplied in high grade bronze (as standard) or with stainless steel option
- Efficient open impeller design - large solids and abrasive materials handled while maintaining high flow rates
- High capacity air handling enables more "well points" to be operated
- Easy on-site handling with solid rubber wheeled chassis and single lifting point
- Patented, spring loaded vacuum pressure gland seal - extended priming efficiency - rapid on-site change in minutes (mechanical seal option)
- Built-in fuel tank for longer running (optional additional fuel tank available)
- Preferred supplier to market leaders in our core sectors - proof of continued high product quality and customer service levels

* subject to geology, fluid density, losses








THE UNIVAC GP & WP EXTENDED LIFE RANGE


UNRIVALLED RELIABILITY FROM SYKES PUMPS

- Extended life components from Sykes Pumps UK (as standard)
- Immediate dispatch of genuine spare parts from our distributor partners or our regional central stores
- Patented, spring loaded vacuum pressure gland seal - changed in minutes
- Lister Petter engines for reliable power source (alternative engines available)
- Long running times with minimal service intervention
- Original British standard for auto self priming pumps - no other priming system maintains such high volumes of air handling
- Solid industrial rubber tyres for high wear resistance and no down time due to punctures
- Bronze internals with stainless steel options for resistance to wear and longer operational life
- All delivering maximum up-time with minimal risk of project delays


GP50/75




GP80




GP100M




WP150-60



GP150M



GP200/GP200M



خانصاحب سايكس
Khansaheb Sykes

www.khansahebsykes.com

Khansaheb Sykes Dewatering
PO Box 13
Dubai
United Arab Emirates
Tel: +971 4 3472120
Fax: +971 4 3473660

Khansaheb Sykes
PO Box 4056
Abu Dhabi
United Arab Emirates
Tel: +971 255 54126
Fax: +971 255 59875

Khansaheb Sykes
PO Box 1848
Sharjah
United Arab Emirates
Tel: +971 653 43453
Fax: +971 653 43908

E-mail: ksykes@khansahebsykes.com

E-mail: adsykes@khansahebsykes.com

E-mail: ksykes@khansahebsykes.com

Disclaimer:

All figures and calculations are approximate and are for guidance purposes only. Sykes Pumps reserves the right to change specification without prior notice, in-line with the policy of continuing product improvements. Images may not be indicative of product to be delivered. Please confirm exact specifications within local quotation.